A-31-1 Legend Boat Launches Ŝ Staging Area Rachel Carso Nat'l Wildlife **Brave Boat Harbor** Collection Point C Water Treatment Intake Refu Kittery / York, ME Permanent Mooring Response Vessel 1,450 Point by Vacuum Truck Skimmer 725 0 Date printed: 9/11/2022 7:01 AM Ĉ ARCHAEOLOGICAL CONFLICTS MAY BE **PRESENT - SEE NARRATIVE** Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, USDA, Maxar, NOAA

A-31-1 Brave Boat Harbor		
Town Kittery / York,	ME	Port Region New Hampshire and Southern Maine
Latitude 43° 05.911 N	Longitude 70° 39.161 W	NOAA Chart # 13283_1
Approx. Tidal Range (fee	et) 9	ESI Map # 54C
Max Current (knots)	Flood Ebb	EVI Map # 3
Source		DeLorme Map # (2019) 1 B5
Resources At Risk		
ESI Primary Shoreline Type Salt to brackish marshes (10A)		
ESI Secondary Shoreline Type Sheltered tidal flats (7)		
Environmental Concerns	Site is located in and immediately adjacent to Rachel Carson National Wildlife Refuge. Contact the U.S. Fish & Wildlife Service in Wells (207) 646-9226 if deploying. Harbor has extensive marshes and mudflats and is a moderately vulnerable shorebird area. Elver run.	
Archaeological Conflicts	No conflict as designed. Deviations from GRS design will 2132.	require MHPC review. Contact MHPC at (207) 287-
Strategy Information		
Strategy Purpose	Divert oil to shore for collection near Old Cart Path Road.	
	 York Harbor Traip Academy boat launch, 12 Williams Ave., Kittery (limited parking) Kittery town boat launch, Pepperell Road, Kittery (not all tide) Pierce's Island boat launch, Portsmouth PNSY (with Navy permission / credentialing) 	
Site Access	By Boat or on foot from Old Cart Path Road, Kittery	
Nearest Boat Ramp	Same as staging areas	
Collection Points	From Old Cart Path Road, Kittery	
Special Instructions	Difficult access	
	Place one 400' section of boom and one 500' section of boom in a cascade configuration from Raynes Neck to Cutts Island as shown	

Recommended Equipment / Resources Length of Boom (feet) 900 Type of Boom 12" - 18" containment boom Recommended Equipment (Minimum) 1 - anchor system with 35 lb. Danforth or equivalent and line for 3:1 scope plus tag line 2 - shoreside connections 1 - workboats (towboats) with minimum 90 hp 1 - boat operators 2 - laborers 2 - laborers 2 - laborers

Unless otherwise indicated, the boom length given is the distance measured on the chart. Actual length required may vary with conditions.